



# ADVANCED LUBRICANTS FOR MERCEDES-BENZ COMMERCIAL VEHICLES



*Mercedes-Benz is the world's largest truck manufacturer, priding itself on providing operators with the latest, most efficient and reliable vehicles. And as one of the world's top lubricant brands, we are committed to developing the highest quality products that meet and often exceed Mercedes specifications, providing outstanding performance and protection for your Mercedes commercial vehicle.*

*Mercedes has developed its own specifications (e.g. MB 228.51 for engine oils) and Texaco® products are approved against these key requirements. In addition, our products cover a full range of approvals for other OEMs, meaning that we can meet the demands of a mix of manufacturers as well as your core Mercedes fleet.*

## **OUR PRODUCTS SUITABLE FOR MERCEDES-BENZ INCLUDE:**

- Heavy duty engine oils from our Ursa® Ultra, Premium and Heavy Duty ranges
- Gear & Axle oils
- Transmission fluids
- Greases
- Coolants

*Please see overleaf for a full table of products*



**Ursa®**  
**Let's go further.™**

# FINDING THE RIGHT PRODUCT FOR YOUR MERCEDES-BENZ VEHICLE

| SPECIFICATIONS  | RELEVANT PRODUCT(S)                                   |  | INDUSTRY STANDARDS              |                                     | PRODUCT ATTRIBUTES |          |            |
|---|---|--|---------------------------------|-------------------------------------|--------------------|----------|------------|
|   | PRODUCT NAME  |  | ACEA*                           | API*                                | Fuel Economy       | Low SAPS | Long Drain |
| <b>ENGINE OILS</b>  |   |  |                                 |                                     |                    |          |            |
| <b>MB 228.51</b>  | Ursa Ultra XLE SAE 5W-30 <sup>1</sup>                 | Premium performance fuel efficient synthetic heavy duty diesel engine lubricant                                    | E6; E9; E7                      | CJ-4; CI-4 Plus; CI-4; SN           | ■                  | ■        | ■          |
|   | Ursa Ultra X SAE 10W-30                               | Premium performance fuel efficient ISOSYN <sup>®</sup> synthetic group II blend heavy duty diesel engine lubricant | E6; E7                          | CI-4                                | ■                  | ■        | ■          |
|   | Ursa Ultra X SAE 10W-40                               | Premium performance ISOSYN synthetic group II blend heavy duty diesel engine lubricant                             | E6; E7                          | CI-4                                |                    | ■        | ■          |
|   | Ursa Ultra S SAE 10W-40 <sup>1</sup>                  | Premium performance synthetic heavy duty diesel engine lubricant   | E6; E7                          | CI-4                                |                    | ■        | ■          |
| <b>MB 228.31</b>  | Ursa Ultra XLE SAE 5W-30 <sup>1</sup>                 | Premium performance fuel efficient synthetic heavy duty diesel engine lubricant                                    | E6; E9; E7                      | CJ-4; CI-4 Plus; CI-4; SN           | ■                  | ■        | ■          |
|   | Ursa Ultra LE SAE 10W-30 <sup>1</sup>                 | Premium performance low SAPS ISOSYN group II technology heavy duty diesel engine lubricant                         | E9                              | CJ-4; SM                            | ■                  | ■        |            |
|   | Ursa Ultra LE SAE 15W-40 <sup>1</sup>                 | Premium performance low SAPS ISOSYN group II technology heavy duty diesel engine lubricant                         | E9; E7                          | CJ-4; CI-4 Plus; CI-4; CH-4; CF; SM |                    | ■        |            |
| <b>MB 228.5</b>   | Ursa Premium TDX (E4) SAE 10W-40                      | High performance semi synthetic heavy duty diesel engine lubricant   | E4; E7                          | CI-4                                |                    |          | ■          |
|   | Ursa Premium TDS SAE 10W-40                           | High performance synthetic heavy duty diesel engine lubricant  | E4; E7                          | CF                                  |                    |          | ■          |
|   | Ursa Premium FE SAE 5W-30                             | High performance synthetic heavy duty diesel engine lubricant  | E4; E7                          | CI-4                                | ■                  |          | ■          |
| <b>MB 228.3</b>   | Ursa Premium TD SAE 10W-40*                           | Proven performance ISOSYN synthetic group II blend heavy duty diesel engine lubricant                              | E7; A3/B4                       | CI-4                                |                    |          |            |
|   | Ursa Premium TD SAE 15W-40                            | Proven performance ISOSYN group II technology heavy duty diesel engine lubricant                                   | E7; A3/B4                       | CI-4                                |                    |          |            |
|   | Ursa Premium TD SAE 20W-50                            | Proven performance extended drain heavy duty diesel engine lubricant   | E7                              | CH-4/SL                             |                    |          |            |
|   | Ursa Heavy Duty SAE 15W-40*, 20W-50*                  | Heavy duty diesel engine lubricants  | E2; A3/B3 <sup>^</sup> (15W-40) | CG-4/SJ                             |                    |          |            |
| <b>MB 226.9~</b>  | Ursa Ultra X SAE 10W-30                               | Premium performance fuel efficient ISOSYN synthetic group II blend heavy duty diesel engine lubricant              | E6; E7                          | CI-4                                |                    |          |            |
|   | Ursa Ultra X SAE 10W-40                               | Premium performance ISOSYN synthetic group II blend heavy duty diesel engine lubricant                             | E6; E7                          | CI-4                                |                    |          |            |
| <b>MB 228.2</b>   | Ursa Heavy Duty SAE 30*, 40*                          | Heavy duty diesel engine lubricants  | E2 <sup>^</sup>                 | CF <sup>^</sup>                     |                    |          |            |
| <b>MB 229.1</b>   | Ursa Premium TD SAE 15W-40                            | Proven performance ISOSYN group II technology heavy duty diesel engine lubricant                                   | E7; A3/B4                       | CI-4                                |                    |          |            |
|   | Ursa Heavy Duty SAE 15W-40*                           | Heavy duty diesel engine lubricant   | E2; A3/B3 <sup>^</sup>          |                                     |                    |          |            |
| <b>MB 235.27</b>  | Ursa Premium TDX (E4) SAE 10W-40 <sup>^</sup>         | High performance semi synthetic heavy duty diesel engine lubricant   | E4; E7                          | CI-4                                |                    |          | ■          |
| <b>MB 235.28</b>  | Ursa Premium FE SAE 5W-30 <sup>^</sup>                | High performance synthetic heavy duty diesel engine lubricant  | E4; E7                          | CI-4                                | ■                  |          | ■          |
| <b>GEAR &amp; AXLE OILS</b>   |   |  |                                 |                                     |                    |          |            |
| <b>MB 235.1</b>   | Geartex EP-A SAE 80W                                  | Proven performance automotive gear lubricant   |                                 | GL-4                                |                    |          |            |
| <b>MB 235.0</b>   | Geartex EP-B SAE 85W-90, EP-C SAE 80W-90 <sup>^</sup> | Proven performance automotive gear lubricants  |                                 | GL-5                                |                    |          |            |
|   | Multigear SAE 80W-90 <sup>^</sup>                     | Proven performance total driveline lubricant   |                                 | GL-4; GL-5; MT-1                    |                    |          |            |
| <b>MB 235.4</b>   | Multigear MTF HD <sup>^</sup>                         | Premium performance heavy duty fully synthetic automotive gear lubricant   |                                 | GL-4                                | ■                  |          | ■          |
| <b>MB 235.11</b>  | Multigear MTF HD <sup>^</sup>                         | Premium performance heavy duty fully synthetic automotive gear lubricant   |                                 | GL-4                                | ■                  |          | ■          |
| <b>MB 235.8</b>   | Syn-Star GL SAE 75W-90 <sup>^</sup>                   | High performance synthetic automotive gear lubricant   |                                 | GL-5; MT-1                          | ■                  |          | ■          |
|   | Multigear S SAE 75W-90                                | High performance fully synthetic total driveline lubricant   |                                 | GL-4; GL-5; MT-1                    | ■                  |          | ■          |
| <b>TRANSMISSION FLUIDS</b>  |   |  |                                 |                                     |                    |          |            |
| <b>MB 236.91</b>  | Synthetic ATF Heavy Duty <sup>^</sup>                 | Premium performance synthetic automatic transmission fluid   |                                 |                                     |                    |          | ■          |
| <b>MB 236.2<sup>^</sup>; MB 236.5<sup>*</sup>; MB 236.7<sup>*</sup></b> | Texamatic 4291  | Proven performance automatic transmission fluid  |                                 |                                     |                    |          |            |
| <b>GREASES</b>  |   |  |                                 |                                     |                    |          |            |
| <b>MB 267</b>   | Multifak EP 2   | Extreme pressure multi-purpose automotive and industrial grease  |                                 |                                     |                    |          |            |
| <b>MB 264.0</b>   | Multifak 264 EP 00/000                                | Extreme pressure lithium grease  |                                 |                                     |                    |          |            |
| <b>MB 265.1</b>   | Hytex EP 2 LF   | High performance long-service (lifetime) multi-purpose grease  |                                 |                                     |                    |          |            |
| <b>Wheel Bearings (SKF)</b>   | Starplex EP 2 <sup>^</sup>                            | High performance long-service multi-purpose grease   |                                 |                                     |                    |          |            |
| <b>COOLANTS</b>   |   |  |                                 |                                     |                    |          |            |
| <b>MB 325.3</b>   | Havoline XLC  | High performance extended life antifreeze coolant  |                                 |                                     |                    |          | ■          |
| <b>MB 325.0</b>   | Havoline GHC <sup>^</sup>                             | Proven performance automotive and industrial engine coolant  |                                 |                                     |                    |          |            |

<sup>^</sup> 'Chevron Recommended'. ~ Obsolete specification. <sup>1</sup> Products suitable for gas engines.

\* Performance – product is either (i) not currently formally approved or certified by the OEM or Industry Standard Organisation; (ii) self-certified; or (iii) was formally approved against an OEM specification which is now obsolete. However, in Chevron's opinion the product is recommended and suitable for use in applications where a product of this specification is required.